



ORCHARD BOOM



Hydraulic folding boom

Three lever hydraulic flow control (all hydraulic pipes included)

250mm horizontal adjustment of boom height (hydraulic)

Robust frame (electroplated)

Manual telescopic width adjustment

Durable 8 mm polypropylene covers

Supplied standard with red or yellow 110 degree plastic nozzles

Mounting components available on request

Standard with three nozzle holder positions per side (250mm apart)

- Labour saving
- Increased flexibility and control of herbicide spray programme
 - Lower overall cost per application
 - Smooth breakaway with replaceable parts
 - Locally manufactured (service and spare parts available)





ONKRUIDSPUITBALK



Hidrolies aangedrewe voubare arm

Drie vlak hidrolies aangedrewe vloei beheer (alle hidroliese pype ingesluit)

250mm horisontale verstelling van arm hoogte (hidrolies)

Stewige raam (elektroplatering)

Monterings komponente beskikbaar op aanvraag

Hand aangedrewe teleskopiese wydte verstelling

Standaard met drie spuitpunt houer posisies per kant (250mm

Duursame 8 mm polipropileen bedekkings

Verskaf standaard met rooi of geel 110 graad plastiek spuitpunte

- Arbeid besparing
- Verhoogde buigsaamheid en beheer van onkruidodder spuit program
 - Laer totale koste per toediening
- Gladde wegbreek met vervangbare parte
- Plaaslik vervaardig (diens en onderdele beskikbaar)

